

Tadiran Coral IPX UCX - Jak jej propojit s 2N® Helios IP

Nastavte 2N® Helios IP i Vaši ústřednu tak, jak jste zvyklí. Podívejte se na příklad níže pro konfiguraci SIP Proxy v 2N® Helios IP.



2N TELECOMMUNICATIONS

SIP Settings

Information

Basic Settings

Advanced Settings

- Network
- Date and Time
- **SIP Settings**
- Web Server
- Audio
- Video
- Audio Codecs
- Video Codecs
- Streaming
- Auto Updates
- Display
- System log
- E-mail

User settings

Display name:

User ID:

Domain:

Use auth ID:

Auth ID:

Password:

Other settings

Local SIP port:

Send keepalive packets:

Starting RTP port:

RTP Timeout: s

SIP proxy settings

Proxy address:

Proxy port:

SIP registration

Register Helios IP:

Registration expires: s

Registrar address:

Registrar port:

SIP Speaker Description	Coral IPX / UCX	CSS
User ID	Extension number	SIP termin ID
Domain	PUGW/CUGW or Sentinel Pro IP address	CSS server or Sentinel Pro IP address
Use Auth ID	Yes	Yes
Auth ID	Extension number	word - default
Password	Defined in IP general or SIP Terminal	12345
Register Helios IP	Yes	Yes
Starting RTP port	30000	30000
Coral IPX / UCX & CSS Description	Coral IPX / UCX	CSS
Class of Service	COS => Transparent_SDP - Yes	---
Multiple Appearance	Key => MultiAppearance - No	User => Feature Config Profile => Call Waiting => Unchecked

Další informace:
Dveřní & Bezpečnostní interkomy (oficiální stránky 2N)